MAXWELL AHD CAMERAS

Commercial Grade

& RECORDERS



2-Year Warranty



Imaging Sensor	1/3" SONY CMOS 2M pixel	
Effective Pixels	1920(H) x 1080(V)	
Dynamic range	90dB	
Video Frame Rate	25 / 30 fps@1080P	
Video format	NTSC / PAL	1/3'
Mini-illumination	0LUX (IR ON)	Color Co
S/N Ration	More than 50dB (with AGC OFF)	🜞 :
OSD	English / Chineses	DAY&NIG
AGC	AUTO	2 x 458
White Balance	AUTO	Sensitivity
Backlight	AUTO	Auto WB
NR	2DNR / 3 DNR / Y-NR / C-RN	Auto White Ba
Brightness	Adjustab l e	≯ (AGC)
Day/Night	EXTERN / INTERNAL / COLOR / MONO	Auto Gain Co
D-WDR	On / Off Selectable	A
Sync code	Internal	BLC
DAY/NIGHT	Support ICR	
Video output	AHD / CVBS	Motion Dete
OPERATING TEMPERATURE	-10°C~50°CRH90% MAX	400
STORAGE TEMPERATURE	-20℃~70℃	0.8.0
Lens	3.6mm Fxied Board Lens	
Input Voltage	12VDC	
IR LEDs	24	
IR LEDs Distance	15M	



VariFocal	Lens	3D-DNR	D-WDR	SMART	IR.	IP67
-----------	------	--------	-------	--------------	-----	-------------

Imaging Sensor	1/3" SONY CMOS 2M pixel	
Effective Pixels	1920(H) x 1080(V)	
Dynamic range	90dB	
VideoFrame Rate	25 / 30 fps@1080P	_
Video format	NTSC /PAL	1/3
Mini-illumiation	0LUX (IR ON)	Color C
S/N Ration	More than 50dB (withGC OFF)	
OSD	English / Chineses	DAY&NI
AGC	AUTO	2 x-256
White Balance	AUTO	Sensitivit
Backlight	AUTO	Aurb: W/B
NR	2DNR / 3DNR /Y-NR / C-RN	Auto White B
Brightness	Adjustable	×acc
Day/Night	EXTERN / INTERNAL / COLOR / MONO	Auto Gain C
D-WDR	On /off Selectable	A
Sync code	Internal	BLC
DAY/NIGHT	Support ICR	
Video output	AHD / CVBS	Motion Det
OPERATINGTEMPERATURE	-10℃~50℃RH90% MAX	400
STORAGETEMPERATURE	-20℃~70℃	0.s.o
Lens	2.8-12mmVarifocal Lens	
Input/oltage	12VDC	
IR LEDs	34	
IR LEDs Distance	20M	



2M. Pixels

Indoor / Outdoor Camera PAC-E1230STL

Home & Office

3D-DNR D-WDR SMART IR IP66

Imaging Sensor	1/3" SONY CMOS 2M pixel	
Effective Pixels	1920(H) x 1080(V)	
Dynamic range	90dB	
Video Frame Rate	25 / 30 fps@1080P	
Video format	NTSC / PAL	
Mini-i ll umination	OLUX (IR ON)	1/3
S/N Ration	More than 50dB (with AGC OFF)	Color
OSD	English / Chineses	*
AGC	AUTO	DAY&N
White Balance	AUTO	2 x - 45
Back l ight	AUTO	Sensitivi
NR	2DNR / 3DNR / Y-NR / C-RN	Aut Wi
Brightness	Adjustable	Auto White
Day/Night	EXTERN / INTERNAL / COLOR / MONO	×46
D-WDR	On / Off Selectable	Auto Gain I
Sync code	Internal	A
DAY/NIGHT	Support ICR	BLO
Video output	AHD / CVBS	
OPERATING TEMPERATURE	-10℃~50℃RH90% MAX	Motion De
STORAGE TEMPERATURE	-20℃~70℃	9 11
Lens	3.6mm Fxied Board Lens	0.5.
Input Voltage	12VDC	
IR LEDs	24	
IR LEDs Distance	15M	



* บันทึกที่ FULL HD ต่อกล้อง @25FPS

* คภาพบันทึกย้อนหลังพ่านสมาร์ทโฟน IOSx , Android และ Kindle

CIF : D1 : 960H : 720P : 1080P Resolution Display 1 : 4 : 5.3 : 8.9 : 20 AHD CIF 360X288 D1 720X576 960H 960X576 720p 1280X720 АНО 2,0 1080p 1920X1080