


RisControl

Smart Touchscreen Keypad



RisControl is a responsive, high resolution 8" touchscreen keypad, offering intuitive easy to use interface. With RisControl the user can control all alarm and cloud-based solutions from RISCO Group from one access point. With a clear overview of the system status, easy arm/disarm functionality and the option to view live video and recordings from the VUpoint Video Solution.

With a design that fits in any space, the keypad is suitable for various residential and commercial applications and offers a perfect opportunity to upgrade and delight your customers.

Keypad functions are presented in an intuitive way allowing users to learn the security system in no time.

RisControl communicates via the System Bus (RS-485) with the control panel. The communication with RISCO Cloud is via WiFi.

The Touchscreen keypad is built for quick and easy installation with a mounting bracket and a detachable connector for easy wiring.

Up to 48 RisControl keypads can be installed on ProSYS Plus. The Touchscreen keypad is supported ProSYS Plus Firmware Version 1.4

Features

- Convenient access of keypad functions for a smart user experience
- Customizable user interface, easy to use
- View live video and recordings by VUpoint Video Solution
- View images Camera Detectors
- Detachable connector for easy wiring.
- Automated Software updates via Wi-Fi
- Grade 3 certified
- P/N RP432KPT000A

The RisControl touchscreen keypad provides home and business owners with an unmatched user experience. With its intuitive smartphone look & feel and self-explanatory icons controlling a security system has never been easier and users can learn their security system in no time.

Users can personalize their interface with quick access icons enabling an easy operation of the security system, video monitoring and home management, allowing each user to create his own set of icons.

RisControl touchscreen keypad provides enhanced security and control allowing user to view live video and recordings from the VUpoint Video Solution.



Technical Specifications

Display	8 " IPS
Resolution	800x1280
Speaker	8 Ohm / 1W
Wi-Fi	802.11 b/g/n 2.4 GHz
System interface	RS-485
Protection	Wall Tamper
Dimensions	208 x 129 x 24mm
Weight	500g
Operating Voltage	13V ±10%
Power consumption	8W
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Standard	EN50131-3, Grade 3 Environmental Class II, PD 6662:2017

SPECIFICATIONS

Operating Voltage	13.8V ±10%
Power consumption	170 mA, 5W max.
Display	8-inch IPS, Resolution 800x1280, Illumination 300 cd/m ²
Type of touch screen	Capacitive touch, 5-point touch control supported
System	Android 7.1.2
CPU	A83T Octa-core Cortex A7
Memory	1G DDR3M RAM, 8G EMMC Flash
Wi-Fi	802.11 b/g/n 2.4 GHz
Bluetooth	BT 4.0, 2.4 GHz
Output Power	20 dBm Max.
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Speaker	1 speaker, 8 Ohm / 1W
Microphone	1xmic
Connections	USB – 1xtype C USB Jack RS-485 – detachable terminal block
Tamper	1xTamper
Dimension	208 x 129 x 24 mm
Weight	481g
Standard	EN50131-3, Grade 3 Environmental Class II, PD 6662:2017
P/N	RP432KPT000A

Z-Wave	EU – 868 MHz IL – 916 MHz US – 908 MHz AU – 921 MHz Output power: 4dBm Max
P/N	RP432KPTZAUA RisControl+ZWave for AU RP432KPTZEUA RisControl+ZWave for EU RP432KPTZILA RisControl+ZWave for IL RP432KPTZUSA RisControl+ZWave for US RP432KPTP00A-RisControl IPS Touchscreen KP+ Proximity

