



# Panda Wireless LCD Keypad

## Description

The 2-Way WL Panda keypad is used to remotely program and operate the RISCO wireless security systems. Being bi-directional, the 2-Way keypad receives a reply status indication from the panel for each command sent to the panel. You can operate the keypad either using a code or a proximity tag.

## TECHNICAL SPECIFICATION

Electrical	
Battery Type	CR123, 3V Lithium battery (x 4) RW332KPP8BTA: 3V, 10 Ah flat Lithium battery (x 1)
Current Consumption	Standby current 9 $\mu$ A, Max current 150 mA
Power Output	868.65MHz: 10 mW
Frequency	433.92, 868.65, 915 MHz
Modulation Type	OOK
Typical Battery Life	3 years
Low battery indication	2.6 V
Proximity RF frequency	13.56 MHz
Physical	
Dimension (HxWxD)	178 x 103 x 38 mm (7 x 4.1 x 1.5")
Weight (Including batteries)	0.435 kg
Environmental	
Operating temperature	-10°C to 55°C (14°F to 131°F)
Storage temperature	-20°C to 60°C (-4°F to 140°F)
Humidity Range	Average relative humidity: 75%
Standard Compliance	EN 50131-1, EN 50131-3 Grade 2, Environmental Class II, EN 50131-6 Type C, EN 50131-5-3

